

ROTOMATIC RM-202

BX, MC & FLEX MOTORIZED
BENCH TOP CUTTERS



RM-202A

U.S. Patents
#4,103,578 & 4,169,400



RM-202M

The heavy-duty ROTOMATICS are the culmination of years of experience in armored cable cutting technology and are used in the production lines of all major armored cable manufacturers

CUT COST ! INCREASE OUTPUT !



The ROTOMATIC drastically cuts labor time insuring clean, fast stripping without damaging the wire inside the cable. Never use a hacksaw again! The open channel construction allows cutting or stripping anywhere along the cable. The heavy-duty production Rotomatics are available with either manual or air actuated clamping systems. The RM-202A uses a large air cylinder to provide smooth and fast cutting action while also preventing operator's fatigue. Simply pressing a button sends the clamping pin down which in turn drives the cable over the power cutting wheel, splitting the armor casing. To remove the armor just untwist the cable and the casing slips off! An adjustable limit stop permits varying the depth of cut for different cables. The RM-202A with a manual lever is ideal when compressed air is not available.

- Ideal for making "Whips" & stripping MC/BX cable in precut lengths
- Great for contractors doing on site finishing work
- Eliminates deburring and nicking of wires
- The open channel construction allows cutting or stripping anywhere along the cable
- Equipped with a top quality gear-motor for extra-long life.
- Adjustable cable guide allows lateral adjustment for different cable pitches
- Other features include fast circular cutter replacement, safety shield lateral cable clamping pin adjustment for different cable pitches

LIMITED WARRANTY: The Rotomatic 202 is warranted to be free from defects in workmanship and material for 90 days from date of original purchase.

PROMOTE SAFETY !

The front of the ROTOMATIC is protected by an unbreakable plexi-glass shield. To insure safe operation the adjustable blade guard is integral to the cutting action and depth of cut setting on the RM-202. The clean cut parallel to the cable axis eliminates deburring of flexible conduit ends. This feature prevents damage to the wire's insulation caused by sloppy manual deburring. For best results we recommend the use of screw clamping and squeeze type connectors. (Check your local electrical code)

	B-108	FOR ALL POWER TOOLS & MACHINES. RS-101-AP, PC-205A, RM-202A, B, C, & M
	LS-105	LUBRICANT STICK FOR BLADES ON ROTOSPLIT & ALL ROTOMATIC MODELS.

- RM-202A, B & C require 40 psi air pressure. Each machine includes a pressure regulator, air gauge & large valve actuator.
- RM-202A cuts 3/8" Flex and 1/2" Flex with pin SP-233.
- RM-202M cuts both 3/8" & 1/2" Flex with pin LP-269. Uses a manually actuated lever to clamp & cut the cable
- RM-202B cuts 3/4" Flex with pin SP-218, 1/2" Flex with SP-233, and 3/8" Flex with pin LP-269.
- RM-202C cuts 1-1/4" Flex with SP-233, cuts 3/4" & 1" Flex with SP-282
- Dimensions: 8"H x 7"W X 11"D, 22 lbs., 115 VAC.
- Accessories: B-108 Replacement Blades; LS-105 Dry Lubricant Stick

*DUE TO THE INCREASE IN PRODUCTIVITY
THE ROTOMATIC PAYS FOR ITSELF
MANY TIMES OVER IN A SHORT TIME*

ROTOMATIC CABLE RANGES	Model	Flex Range	Standard Pin	Optional	AWG Range	O.D. Range
	RM-202A	3/8" TO 1/2"	3/8" LP-269	1/2" SP-233	#14-2 TO #4-4	0.42" TO 0.92"
	RM-202M	3/8" TO 1/2"	3/8" & 1/2" LP-269	-----	#14-2 TO #4-4	0.42" TO 0.92"
	RM-202B	3/8 TO 3/4"	3/4" SP-218	3/8" LP-269 1/2" SP-233	#14-2 TO #2-4	0.42" TO 1.10"
	RM-202C	3/4" TO 1-1/4"	1-1/4" SP-233	3/4" TO 1" SP-282	#4-4 TO #1-3	1.00" TO 1.70"

ON THE INTERNET LOG ON TO www.SEATEKCO.com - WHERE QUALITY & SMART ENGINEERING COME TO LIFE!



A SMALL COMPANY WITH BIG IDEAS®

392 PACIFIC STREET, STAMFORD, CT 06902

PHONE: (203) 324-0067 P FAX: (203) 324-7844 P www.SeatekCo.com

