



FOR INSPIRED ARCHITECTURE

SPECIFICATION DATA SHEET - AXOLOTL PAINT Clear Acrylic Sealer **For the information of Specifiers and Trades**

Product description

Axolotl Clear Acrylic Sealer is a non – yellowing matt clear protective sealant for use internally over most Axolotl Paint products. The low VOC acrylic formulation is designed to repel water reducing dirt pick up and improving washability. Particularly recommended for flat finishes in high traffic areas.

Clear Acrylic Sealer substrate preparation

Clear Acrylic Sealer is formulated for direct application to completely dry Axolotl Paint products such as Micaceous, Chroma Flat, and Metta. Suitable for interior use only.

Applying Clear Acrylic Sealer

Stir well and apply 1 - 2 coats of Clear Acrylic Sealer by brush or spray. Clear Acrylic Sealer is a fast drying paint, take care to maintain a wet edge during application, and avoid reworking drying surface, or lapping may be evident. Care should be taken to avoid painting back over areas that may have started drying off as it can create a milky appearance, particularly when coating over Metta and darker colours. To help maintain a wet edge and achieve a clean appearance the first coat can be thinned with up to 25% water.

Drying time is typically 30 minutes to touch dry, 2 hours to recoat. Full cure after 7 days.

Approximate coverage is 9 - 12 m2 per litre per coat.

General precautions

Paint application

Clear Acrylic Sealer will change the appearance of the base paint by intensifying colour and providing a low sheen finish, it is recommended to test before proceeding. Suitable for internal applications only.

Temperature

Axolotl Clear Acrylic Sealer should not be applied where surface or air temperature is below 10°C or above 35°C. Excessively fast drying can occur if painting hot surfaces or in direct sunlight.

Initial protection

Adequate protection should be provided against rain and sub-zero temperatures for a period of not less than 24 hours after application. Protection against mechanical abrasion should be provided for at least 7 days after application.

Packaging

Axolotl Clear Acrylic Sealer is available in 1, 4, 10 & 15 litre containers.

NOTE FOR SPECIFIERS -

PLEASE ENSURE SPECIFICATION SHEET IS COPIED & ATTACHED TO TENDER DRAWINGS FOR THE REFERENCE OF ALL RELEVANT TRADES.

For further information, technical assistance or costing please contact:

Company	Axolotl Group Pty Ltd
Address	6 / 73 Beauchamp Road, Matraville, N.S.W, 2036.
Phone	02 9666 1207
Email	info@axolotl.com
Website	www.axolotlpaint.com