


### BOARD PROFILE:

	4mm Oak Top Layer	300-1500mm Random Length Boards
	12mm Multiply Core	Width 125mm
	2mm Backing Board	

### PRODUCT DIMENSIONS & HANDLING:

<b>Board Depth:</b>	18mm	<b>Pack Size:</b>	2.20m <sup>2</sup>
<b>Board Width:</b>	125mm	<b>Pack Weight:</b>	25kg
<b>Board Length:</b>	Random Lengths	<b>Packs Per Pallet:</b>	52

### BOARD DETAIL:

<b>Type of Board:</b>	Engineered Flooring		<b>Fix System:</b>	T&G
<b>Finish:</b>	Lacquered	Oiled	<b>Grade:</b>	ABCD
<b>Density of Finish:</b>	120	45	<b>Janka Reading:</b>	1360
<b>Bevel Detail:</b>	G04		<b>Core Material:</b>	Eucalyptus / Poplar

### MANUFACTURER TESTING:

<b>Manufacturer Tolerance:</b>	EN13647	<b>Thermal Conductivity:</b>	Awaiting SGS Test Results
<b>Moisture Content:</b>	EN13183-1 (6-10%)	<b>Formaldehyde:</b>	EN717-1
<b>Fire Resistance:</b>	EN13501-1	<b>CE Mark</b>	EN13489
<b>ISO 9001:</b>	Complaint	<b>EUTR:</b>	EUTR Compliant




### MISC ITEMS:

<b>Warranty:</b>	Residential - 20 Years		Commercial - On Application			
<b>Oak Origin:</b>	Europe		<b>Manufactured In:</b>	P.R.C		
<b>Installation:</b>	✓	Float	✓	Bond	✓	Nail
<b>Under Floor Heating:</b>	Suitable for UFH / Max contact temperature to the base of the board must not exceed 26°C. Waterborne or Electric Embedded Systems only					

### ACCREDITATIONS:



### BOARD PROFILE:

	4mm Oak Top Layer	300-1500mm Random Length Boards
	12mm Multiply Core	Width 150mm
	2mm Backing Board	

### PRODUCT DIMENSIONS & HANDLING:

<b>Board Depth:</b>	18mm	<b>Pack Size:</b>	1.65m <sup>2</sup>
<b>Board Width:</b>	150mm	<b>Pack Weight:</b>	20.8kg
<b>Board Length:</b>	Random Lengths	<b>Packs Per Pallet:</b>	70

### BOARD DETAIL:

<b>Type of Board:</b>	Engineered Flooring		<b>Fix System:</b>	T&G
<b>Finish:</b>	Lacquered	Oiled	<b>Grade:</b>	ABCD
<b>Density of Finish:</b>	120	40-60	<b>Janka Reading:</b>	1360
<b>Bevel Detail:</b>	G04		<b>Core Material:</b>	Eucalyptus

### MANUFACTURER TESTING:

<b>Manufacturer Tolerance:</b>	EN13647	<b>Thermal Conductivity:</b>	Awaiting SGS Test Results
<b>Moisture Content:</b>	EN13183-1 (8-10%)	<b>Formaldehyde:</b>	E1
<b>Fire Resistance:</b>	DFL-S1	<b>CE Mark</b>	EN13489
<b>ISO 9001:</b>	Complaint	<b>EUTR:</b>	EUTR Compliant

### MISC ITEMS:

<b>Warranty:</b>	Residential - 20 Years		Commercial - On Application			
<b>Oak Origin:</b>	Europe		<b>Manufactured In:</b>	P.R.C		
<b>Installation:</b>	✓	Float	✓	Bond	✓	Nail
<b>Under Floor Heating:</b>	Suitable for UFH / Max contact temperature to the base of the board must not exceed 26°C. Waterborne or Electric Embedded Systems only					

### ACCREDITATIONS:

