


BOARD PROFILE:

	4mm Walnut Top Layer	400-1200mm Random Lengths
	12mm Multiply Core	Width 125mm
	2mm Backing Board	

PRODUCT DIMENSIONS & HANDLING:

Board Depth:	18mm	Pack Size:	2.20m ²
Board Width:	125mm	Pack Weight:	25kg
Board Length:	Random Lengths	Packs Per Pallet:	52

BOARD DETAIL:

Type of Board:	Engineered Flooring	Fix System:	T&G
Finish:	Lacquered	Grade:	ABCD
Density of Finish:	80-100	Janka Reading:	1360
Bevel Detail:	G04	Core Material:	Eucalyptus

MANUFACTURER TESTING:

Manufacturer Tolerance:	EN13647	Thermal Conductivity:	EN14342
Moisture Content:	EN13183-1 (6-10%)	Formaldehyde:	EN717-1
Fire Resistance:	EN13501-1	CE Mark	EN13489
ISO 9001:	Complaint	EUTR:	EUTR Compliant


MISC ITEMS:

Warranty:	Residential - 20 Years	Commercial - On Application				
Walnut Origin:	USA	Manufactured In:	P.R.C			
Installation:	✓	Float	✓	Bond	✓	Nail
Under Floor Heating:	Suitable for UFH / Max contact temperature to the base of the board must not exceed 26°C. Waterborne or Electric Embedded Systems only					

ACCREDITATIONS:



BOARD PROFILE:

	4mm Walnut Top Layer	Fixed Length Boards
	12mm Multiply Core	Width 150mm
	2mm Backing Board	1870mm

PRODUCT DIMENSIONS & HANDLING:

Board Depth:	18mm	Pack Size:	1.403m ²
Board Width:	150mm	Pack Weight:	15.85kg
Board Length:	1870mm	Packs Per Pallet:	70

BOARD DETAIL:

Type of Board:	Engineered Flooring	Fix System:	T&G
Finish:	Lacquered	Grade:	ABCD
Density of Finish:	80-100	Janka Reading:	1360
Bevel Detail:	G04	Core Material:	Eucalyptus

MANUFACTURER TESTING:

Manufacturer Tolerance:	EN13647	Thermal Conductivity:	Awaiting SGS Test Results
Moisture Content:	EN13183-1 (6-10%)	Formaldehyde:	EN717-1
Fire Resistance:	EN13501-1	CE Mark	EN13489
ISO 9001:	Complaint	EUTR:	EUTR Compliant


MISC ITEMS:

Warranty:	Residential - 20 Years	Commercial - On Application
Walnut Origin:	USA	Manufactured In: P.R.C
Installation:	<input checked="" type="checkbox"/> Float	<input checked="" type="checkbox"/> Bond <input checked="" type="checkbox"/> Nail
Under Floor Heating:	Suitable for UFH / Max contact temperature to the base of the board must not exceed 26°C. Waterborne or Electric Embedded Systems only	

ACCREDITATIONS:



BOARD PROFILE:

	4mm Walnut Top Layer	Fixed Length Boards
	12mm Multiply Core	Width 191mm
	2mm Backing Board	1870mm

PRODUCT DIMENSIONS & HANDLING:

Board Depth:	18mm	Pack Size:	2.143m ²
Board Width:	191mm	Pack Weight:	24.22kg
Board Length:	1870mm	Packs Per Pallet:	45

BOARD DETAIL:

Type of Board:	Engineered Flooring	Fix System:	T&G
Finish:	Treffert Oil	Grade:	ABCD
Density of Finish:	40-60	Janka Reading:	1360
Bevel Detail:	G04	Core Material:	Eucalyptus

MANUFACTURER TESTING:

Manufacturer Tolerance:	EN13647	Thermal Conductivity:	EN14342
Moisture Content:	EN13183-1 (6-10%)	Formaldehyde:	EN717-1
Fire Resistance:	EN13501-1	CE Mark	EN13489
ISO 9001:	Complaint	EUTR:	EUTR Compliant

MISC ITEMS:

Warranty:	Residential - 20 Years	Commercial - On Application
Walnut Origin:	USA	Manufactured In: P.R.C
Installation:	<input checked="" type="checkbox"/> Float <input checked="" type="checkbox"/> Bond	<input checked="" type="checkbox"/> Nail
Under Floor Heating:	Suitable for UFH / Max contact temperature to the base of the board must not exceed 26°C. Waterborne or Electric Embedded Systems only	

ACCREDITATIONS:

