



DECLARATION OF PERFORMANCE

DOP M23-002

1. Unique identification code of the product-type:

Parquet flooring according to EN 13489

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

PC 350 | UV-oiled, PD 400 Cottage | UV-oiled, PS 300 | UV-oiled, PC 300 | UV-oiled, PD 550 | UV-oiled, PD 200 | UV-oiled, PD 450 | UV-oiled, PQ 500 | UV-oiled | Edition M2

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14342) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MeisterWerke Schulte GmbH, Johannes-Schulte-Allee 5, D-59602 Ruethen-Meiste

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

Textiles & Flooring Institute GmbH, Charlottenburger Allee 41,
D-52068 Aachen, Test report 360937-02

not applicable





ihd GmbH, Zellescher Weg 24,
D-01217 Dresden, Test report 155431-1, 158027-1
Notified Body

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Bulk density and thickness	>500 kg/m ³ , >10 mm	EN 14342:2012
Fire behaviour	 D _{fl} s1	EN 14342:2012
Formaldehyde Emission Class	 E1	EN 14342:2012
Content of Pentachlorophenol	 ≤ 5 ppm	EN 14342:2012
Breaking strength	NPD	EN 14342:2012
Slip resistance	NPD	EN 14342:2012
Thermal conductivity [W/mK]	 ≤ 0,14 W/mK	EN 14342:2012
Biological durability	NPD	EN 14342:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4
Signed for and on behalf of the manufacturer by:

Hans Nold, Head of Quality Management
(name and function)

D-59602 Ruethen-Meiste, August, 18th 2014
(place and date of issue)

(signature)