





BOARD PROFILE:

	4mm Oak Top Layer	Random Length Boards		
	12mm Multiply Core			Width 150mm
	2mm Backing Board			

PRODUCT DIMENSIONS & HANDLING:

Board Depth:	18mm	Pack Size:	1.65m ²
Board Width:	150mm	Pack Weight:	22kg
Board Length:	400-1500mm (Random Length)	Packs Per Pallet:	50

BOARD DETAIL:

Type of Board:	Structural Engineered Oak		Fix System:	T&G
Finish:	Lacquered	Oiled	Grade:	ABCD
Density of Finish:	80-100	30-35	Janka Reading:	1360
Bevel Detail:	G04 Bevel		Core Material:	Poplar / Birch (Multiply)

MANUFACTURER TESTING:

Manufacturer Tolerance:	EN13647	Thermal Conductivity:	EN14342
Moisture Content:	EN13183-1 (7-10%)	Formaldehyde:	EN717-1
Fire Resistance:	EN13501-1	CE Mark	EN13489
ISO 9001:	Complaint	EUTR:	Compliant

MISC ITEMS:

Warranty:	20 Years - Residential		On Application - Commerical			
Oak Origin:	Europe		Manufactured In:	P.R.C		
Installation:	✓	Float	✓	Bond	✓	Nail
Under Floor Heating:	Suitable for UFH if installed as floating floor with DPM underlay Manifold temp must not exceed 26°C					

ACCREDITATIONS:

