

# PIG Well Pad Liner - 130 mil

## Product Information:

Cover your drill site with this ultra-durable, composite liner to protect workers and the environment.

- Goes down as a single layer — eliminates multiple-layer installation
- Polypropylene composite consists of three barrier films sandwiched by two layers of needle-punched geotextile with heat-fused surfaces
- Offers 3X more tear resistance and 5X more puncture resistance than standard 30-mil HDPE liners
- Absorbs nuisance leaks, drips and spills on contact, and embedded barrier films keep all spills from reaching the ground
- High-traction surface minimizes slip-and-fall injuries in wet or dry conditions
- Versatile liner can be used to create secondary containment structures on-site for frac tanks, cylindrical tanks and drill cuttings
- Welds easily for liquid-tight installation
- Recyclable to reduce waste
- Won't stretch or crack like HDPE

PIG Well Pad Liner – 130 mil			
Item #	Master Roll Approx. Dimensions	Approx. Weight	Color
<b>MAT7000</b>	18'W x 450'L	1,615 lbs.	Dark Gray
<b>MAT7004</b>	12'W x 300'L	730 lbs.	Dark Gray
<b>MAT7010</b>	6'W x 920'L	1,085 lbs.	Dark Gray
<b>MAT7600</b>	18'W x 450'L	1,615 lbs.	Light Gray

Always in stock. 24/7 customer service. Contact your New Pig Energy sales representative for pricing details.

**Need a custom solution for your drilling operation?  
Call the New Pig Energy secondary containment experts at 1-855-PIG-LINER (744-5463).**

See back for additional product specifications.



**Phone: 1-855-PIG-LINER**  
**Email: [pigliner@newpigenergy.com](mailto:pigliner@newpigenergy.com)**  
**Online: [newpigenergy.com](http://newpigenergy.com)**

330377

PIG, PIG logo are registered trademarks in USA and other countries. See [tm.newpig.com](http://tm.newpig.com)

# PIG Well Pad Liner - 130 mil

## Product Specifications:

	<b>MAT7000</b>	<b>MAT7004</b>	<b>MAT7010</b>	<b>MAT7600</b>
Composition:	Polypropylene	Polypropylene	Polypropylene	Polypropylene
Color:	Dark Gray	Dark Gray	Dark Gray	Light Gray
UV Resistant:	Yes	Yes	Yes	Yes
Master Roll Width:	18' (5.5 m)	12' (3.7 m)	6' (1.8 m)	18' (5.5 m)
Thickness:	130 mil	130 mil	130 mil	130 mil
Approximate Roll Length:	450' (137.2 m)	300' (91.4 m)	920' (280.4 m)	450' (137.2 m)
Approximate Roll Weight:	1,615 lbs. (732.6 kg)	730 lbs. (331.1 kg)	1,085 lbs. (492.1 kg)	1,615 lbs. (732.6 kg)
Core dia.:	4" (10.2 cm)	4" (10.2 cm)	3" (7.6 cm)	4" (10.2 cm)
Recyclable:	Yes	Yes	Yes	Yes

## Testing Information:

MATERIAL	THICKNESS	TENSILE PROPERTIES (MAX STRENGTH)		PUNCTURE RESISTANCE	TEAR RESISTANCE	
		A-Break lb/in-width	B-Break lb/in-width		A	B
PIG Well Pad Liner - 130 mil	ASTM D 5994	ASTM D 6693/GRI, 2 ipm rate		ASTM D 4833	ASTM D 1004 (lbs.)	
	Mils			(lbs.)		
	144	161	100	272	67	59

**Top Side Absorbency: Water = 3.31 gal./100 sq. ft.; Oil = 3.42 gal./100 sq. ft.**

**Permittivity (ASTM D 4491) = 0**

**Calculated Darcy Coefficient of Permeability = 0**



**New Pig Energy**

*Secondary Containment  
from the Leak & Spill Experts.™*

**Phone: 1-855-PIG-LINER**

**Email: [pigliner@newpigenergy.com](mailto:pigliner@newpigenergy.com)**

**Online: [newpigenergy.com](http://newpigenergy.com)**

330377

PIG, PIG logo are registered trademarks in USA and other countries. See [tm.newpig.com](http://tm.newpig.com)