

## LUGGAGE TAGS

12" X 3.5" CUT OF FABRIC FOR LOOP

12" X 1.5" CUT OF FABRIC FOR TAG

2.5" X 4" CUT OF PLASTIC FOR POCKET

12" X 3" CUT OF IRON ON INTERFACING

FOLD LOOP IN HALF LENGTHWISE AND IRON. OPEN. FOLD AND IRON BOTH SIDES TO CENTER. PRESS LINE. REFOLD SO LOOP IS 3/8" WIDE. STITCH CLOSE TO EDGE.

SHAPE INTERFACING USING TEMPLATE.

INTERFACING WILL BE 1/4" SMALLER THAN TAG. CENTER AND IRON INTERFACING TO TAG FABRIC.

FOLD EXTRA TAG FABRIC BACK OVER INTERFACING AND IRON.

FOLD TAG IN HALF. INSERT LOOP AT TOP. SEW CLOSE TO EDGE AROUND TAG. GO BACK AND FORTH SEVERAL TIMES OVER LOOP ENDS TO SECURE WELL.

CENTER PLASTIC ON TAG. STICH THREE SIDES TO FORM POCKET FOR BUSINESS CARD.

CONGRATULATIONS. YOU HAVE CREATED A LUGGAGE TAG.