



62 Wax

PRODUCT DATA

Description

Traditional toluene based wax polish for finishing furniture. Very quick drying, can be buffed to a very high gloss.

Area of use

Furniture

Substrates

Wood

Packing

450ml and 5 litres

Physical Constants

Colour:	Antique Pine
Finish:	Gloss
Volume solids:	28%
Theoretical spreading rate:	8 – 10 sq metres per litre
Flash point:	4°C
Specific gravity:	0.80
Dry to touch:	5 – 10 minutes
Overcoating time:	15 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Cloth
Thinner:	N/A
Cleaning of tools:	Toluene

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393