



Acrylic Primer Undercoat

PRODUCT DATA

Description

A water thinned combined primer and undercoat with excellent adhesion and opacity, for use on all types of non-ferrous surfaces. Ideal for plaster, brick or cement but is particularly suitable for wood. Specially recommended for situations where speed of application, economy or low odour during the drying process is important.

Area of use

Interior and exterior

Substrates

Wood, brick, plaster and cement

Packing

1 litre and 2.5 litre (min batch 120 litres)

Physical Constants

Colour:	White
Finish:	Matt
Volume solids:	48%
Theoretical spreading rate:	12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.25
Dry to touch:	2 hours (20°C)
Overcoating time:	4 - 8 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	Water
Cleaning of tools:	Water

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.