



Anti Rugine (MIO)

PRODUCT DATA

Description

High quality one coat anti-rust metal paint. Based on Micaceous Iron Oxide. This high build primer is suitable either for brushing or spraying purposes. Provides excellent adhesion to ferrous metals and imparts good water resistance.

Area of use

Interior and exterior

Substrates

Ferrous metal

Packing

5 litres

Physical Constants

Colours:	Black
Finish:	Matt
Volume solids:	50%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.3
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush or conventional and airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393