



Aqualac Joint Filler

PRODUCT DATA

Description

Quick drying joint filler for use prior to applying aqualac floor finish. After sanding, sawdust can be mixed with joint filler to fill larger joints to give a natural finish.

Area of use

Wooden floors

Substrates

Wood

Packing

2.5 litres and 5 litres

Physical Constants

Colour:	Clear
Finish:	Semi Matt
Volume solids:	30%
Theoretical spreading rate:	15 sq.metres per litre
Flash point:	12°C
Specific gravity:	0.97
Dry to touch:	5 – 10 minutes
Overcoating time:	1 – 2 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Pallet Knife or Scraper
Thinner:	Cellulose Thinners
Cleaning of tools:	Cellulose Thinners

<u>Surface condition</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.
---------------------------------	--

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.