



Aquapolish

PRODUCT DATA

Description:

A water based wax for use as a reviver for wood floors which have been coated with Aqualac water based lacquer. Easy to use. Simply apply using a soft clean cloth or a suitable mop and polish off to leave a Semi Matt Finish.

Area of use:

Internal

Substrates:

Wood flooring

Packing:

5 Litre

Physical Constants:

Colour:	Light Amber
Finish:	Semi Matt Wax
Volume solids:	20%
Theoretical spreading rate:	20 sq.metres per litre
Flash point:	N/A
Specific gravity:	1.00
Dry to touch:	30 minutes
Overcoating time:	N/A

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Cloth or mop
Thinner:	
Cleaning of tools:	Water

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393