



## Asipo Dampstain Proofer

### PRODUCT DATA

---

#### Description

Mica water based coating is designed to stop manifestation of salts and discoloration of the painted surface; this would also seal the surface and prevent stains coming through decoration.

#### Area of use

Internal walls and ceilings

#### Substrates

Plaster

#### Packing

5 litres (min batch 150L)

#### Physical Constants

Colour:	Pale Blue
Finish:	Matt
Volume solids:	54%
Theoretical spreading rate:	10 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.16 – 1.18
Dry to touch:	1 – 2 hours
Overcoating time:	4 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method:	Brush only
Thinner:	N/A
Cleaning of tools:	Water

**Surface condition** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

*Please check colour before use. If using multiple cans please check batch numbers are the same.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.