



Chlorinated Rubber

PRODUCT DATA

Description

A very hard-wearing chemically resistant paint. Ideal where conditions require a degree of chemical and water resistance typical examples would be swimming pools, manhole covers and metal tanks. It is also excellent for road markings where high visibility and durability is a must.

Area of use

Interior and exterior

Substrates

Concrete, ferrous metal, manhole covers and road surfaces

Packing

5 litres

Physical Constants

Colours: Yellow 10E53 and White
(other colours on request min batch 200L)

Finish: Semi gloss

Volume solids: 55%

Theoretical spreading rate: 15 sq. metres per litre

Flash point: 23°C

Specific gravity: 1.3 – 1.4

Dry to touch: 1 - 2 hours (20°C)

Over-coating time: 16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method: Brush, roller, conventional and airless spray
Thinner: Xylene
Cleaning of tools: Xylene

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393