



## FLAG Primer/Undercoat

### PRODUCT DATA

---

#### Description

A one coat high quality undercoat/primer alkyd resin system for use under Flag Gloss and other Alkyd based topcoats. The product is ideally suited for kitchens and bathrooms, doors, window frames, furniture and woodwork in general. Also ideal for metal surfaces. It is easy to apply and provides excellent coverage.

#### Area of use

Interior and exterior.

#### Substrates

Metal surfaces, woodwork, fiberboards etc.

#### Packing

1 litre and 2.5 litres

#### Physical Constants

Colours:	White and Grey
Finish:	Matt
Volume solids:	50%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.4
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

#### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.*

*For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.