



Flag Gloss

PRODUCT DATA

Description

A high quality finish alkyd resin system suitable for kitchens and bathrooms, doors, window frames, furniture and woodwork in general. Also ideal for metal surfaces. Designed for top-class work where the highest standards of finish, durability and colour retention are required.

Area of use

Interior and exterior.

Substrates

Metal surfaces, woodwork, fibreboards etc.

Packing

1 litre and 2.5 litres (min batch 150L)

Physical Constants

Colours:	Black, White, Magnolia or special colours
Finish:	High gloss
Volume solids:	40%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.1
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats. Undercoat may be required.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.