



Vinyl Emulsion

PRODUCT DATA

Description

A vinyl copolymer water based product with excellent coverage, tough and durable, formulated to cover extremely well to concrete and wood, intended for the decoration of walls and ceilings where maximum washability and resistance to wear and tear are required, easy to apply and very easy to wash down after it has dried.

Area of use

Interior and exterior.

Substrates

Cementitious, plaster, block work, wood etc

Packing

1litre, 2.5 litres and 5 litres (1 litre and 2.5 litres min batch 150L)

Physical Constants

Colours: White, Magnolia and special colours

Finish: Matt and Silk

Volume solids: 48%

Theoretical spreading rate: 12 sq. metres per litre

Flash point: N/A

Specific gravity: 1.4

Dry to touch: 2 hours (20°C)

Overcoating time: 4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method: Brush, roller, conventional and airless spray

Thinner: Water

Cleaning of tools: Water

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.