



French Polish (Brown)

## PRODUCT DATA

---

### Description

Most commonly used French polish for use on dark woods, or where lightwoods need to be slightly coloured. Can be mixed with transparent or white polish to provide a hint of colour.

### Area of use

Interior and exterior.

### Substrates

Wood

### Packing

500ml and 5 litres

### Physical Constants

Colour:	Brown
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	18 sq. metres per litre
Flash point:	38°C
Specific gravity:	0.85
Dry to touch:	5 – 10 minutes (20°C)
Overcoating time:	15 – 20 minutes

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### Application Details

Application method:	Cloth or Pad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Use a shellac sanding sealer to give a smooth surface prior to using brown French polish.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.