



## General Purpose Varnish

### PRODUCT DATA

---

#### Description

A traditional based alkyd resin varnish formulated to provide a flexible and durable external finish with good UV resistance.

#### Sealing/Priming

Thin with 10% white spirit for initial coats on new or porous timber.

#### Area of use

Interior and exterior

#### Substrates

Wood

#### Packing

1 litre, 2.5 litres or 5 litres (min batch 100 litres)

#### Physical Constants

Colour:	Clear
Finish:	Gloss
Volume solids:	40%
Theoretical spreading rate:	16 sq metres per litre
Flash point:	38°C
Specific gravity:	0.92
Dry to touch:	4 – 6 hours
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method:	Brush, conventional or airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

#### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.