



Gilt Wax

## PRODUCT DATA

---

### Description

Metallic paste wax for gilding picture frames, artefacts etc.

### Area of use

Picture frames, artifacts etc.

### Substrates

Wood, plaster, board

### Packing

50ml and 5 litres (special order batch quantity)

### Physical Constants:

Colour:	Bronze and Pewter
Finish:	Semi Gloss
Volume solids:	35%
Theoretical spreading rate:	6 – 8 sq.metres per litre
Flash point:	18°C
Specific gravity:	1.00
Dry to touch:	10 – 15 minutes

Overcoating time:

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### Application Details

Application method:	Cloth
Thinner:	
Cleaning of tools:	

### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

*Please check colour before use. If using multiple cans please check batch numbers are the same.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393