



Liming Wax

PRODUCT DATA

Description

Paste wax to give a limed finish grain, particularly on oak doors or cabinets. Buff to a gloss finish.

Area of use

Furniture

Substrates

Wood

Packing

250ml and 450ml

Physical Constants

Colour:	White
Finish:	Gloss
Volume solids:	30%
Theoretical spreading rate:	6 – 8 sq.metres per litre
Flash point:	38°C
Specific gravity:	1.1
Dry to touch:	30 minutes
Overcoating time:	

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Cloth
Thinner:	N/A
Cleaning of tools:	White Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.