



Red/Grey Oxide Quick Drying Primer

PRODUCT DATA

Description

A high build oxide primer with quick drying properties. An anti-corrosive primer suitable for either brush or spray application. The primer gives excellent adhesion to ferrous metals. Can be over coated at any period of time after the recommended drying time. Suitable for use with a wide variety of top coats.

Area of use

Interior and exterior.

Substrates

Ferrous metal

Packing

1 litre, 2.5 litres and 5 litres (1 litre and 2.5 litres min batch 100 litres)

Physical Constants

Colours:	Red and Grey
Finish:	Matt
Volume solids:	50%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.3 – 1.4
Dry to touch:	2 - 4 hours (20°C)
Over-coat:	8 - 16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.