



Premium Shed & Fence Treatment

PRODUCT DATA

Description

A high quality satin based wood finish. Based on a good quality flexible resin this product will protect and waterproofs timber. Premium treatment gives a long lasting durable finish and premium quality. No primer required.

Area of use

Exterior

Substrates

Wood fencing, shed and general timber

Packing

5 litres and 20 litres (supplied as 4 x 5L)

Physical Constants

Colour:	Light, Medium and Dark Brown and Red Cedar
Finish:	Satin
Volume solids:	20%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	42°C
Specific gravity:	0.83
Dry to touch:	2 - 4 hours
Over-coating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	N/A
Cleaning of tools:	White Spirit

Surface Condition

Surface should be clean, dry and free of dust, dirt and other contamination. Remove any loose and defective paint. Mould, lichen and algae should be removed with a suitable treatment prior to application.

Please refer to the Material Safety Data Sheet for further information.

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.