



Spirit Stains (Methylated Spirit)

PRODUCT DATA

Description

Light fast stains for use on furniture prior to polishing or waxing.

Area of use

Interior

Substrates

Wood

Packing

5 litres

Physical Constants

Colour: Light or Dark Oak, Black, Rosewood and Mahogany

Finish: Matt

Volume solids: N/A

Theoretical spreading rate: 15 – 20 sq.metres per litre

Flash point: 18°C

Specific gravity: 0.80

Dry to touch: 15 minutes

Overcoating time: 1 hour

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method: Brush or cloth

Thinner: N/A

Cleaning of tools: Methylated Spirit

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.