



## Stabilising Solution

### PRODUCT DATA

---

#### Description:

Clear stabilising and penetrating sealer to bind friable and chalky substrates prior to coating with masonry paints.

#### Area of use:

Interior and exterior

#### Substrates:

Rendering and plaster

#### Packing:

5 Litres

#### Physical Constants:

Colour:	Slightly amber
Finish:	-
Volume solids:	-
Theoretical spreading rate:	8-10 sq. metres per litre
Flash point:	42°C
Specific gravity:	0.85
Dry to touch:	2-4 hours
Over-coating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush
Thinner:	N/A
Cleaning of tools:	White Spirit

**Surface Condition:** Wire brush surface to remove all flaking materials. Ensure surface is free from dust, algae and mould before application.

*Please refer to the Material Safety Data Sheet for further information.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393