



## Quick Drying Polyurethane Varnish

### PRODUCT DATA

---

#### Description:

Quick drying varnish giving a hard durable gloss finishes. Ideal for commercial use where speed of drying is essential.

#### Area of use:

Interior and exterior

#### Substrates:

Wood

#### Packing:

5 Litre

#### Physical Constants:

Colour:	Clear
Finish:	Gloss
Volume solids:	42%
Theoretical spreading rate:	16 sq.metres per litre
Flash point:	36°C
Specific gravity:	0.92
Dry to touch:	1 - 2 hours
Overcoating time:	4 - 6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.