



Black Bitumen

PRODUCT DATA

Description

Black bitumen is based on a high quality bitumen that's dissolved in a special blend of petroleum solvents. It provides excellent protection against anti-rust, waterproofing and has good resistance to diluted acids and alkalis on a wide range of materials especially iron and steel. Conform to B.S. 3416:1988 TYPE 2

Use for protecting and preserving iron and steel fabrications, iron castings, timber, concrete. Including rainwater pipes and guttering, railings, corrugated iron sheets, roofs, manhole covers, storage tanks, pipe work, piling, concrete posts and fencing. Car, caravan and vehicle chassis work. Agricultural buildings, barns etc. Suitable for drinking water tanks, interior and exterior if used in accordance with B.S. instructions.

Area of use

Exterior

Substrates

Concrete, stone and ironwork

Packing

5 litres

Physical Constants

Colour:	Black
Finish:	Semi gloss
Volume solids:	42%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	0.94
Dry to touch:	6 hours (20°C)
Over-coating time:	16 - 24 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.