



PRODUCT DATA

Description:

Copper based antifouling. FLAG Performance Extra Antifouling is semi-hard to enable use in most craft up to 30 knots but still able to refresh its surface with some mild erosion. Proven performance for all types of fouling in all waters. Thoroughly tested with proven performance in some of the toughest waters in the world. This product is self-priming when topping-up existing (similar copper based) antifouling; otherwise FLAG Multi-Purpose Metallic Primer is required. Also suitable for long distance cruisers or racers due to the semi-hard nature of the paint system.

Area of use:

Boat hulls

Substrates:

GRP, wood, steel and ferro cement. Not suitable for aluminum or galvanised surfaces.

Packing:

2.5 litre (other sizes available on special request)

Physical Constants:

Colour: Black, Dark Blue, Red and Steel White

Finish: Matt

Volume solids: 72%

Theoretical spreading rate: 10 sq.metres per litre

Flash point: 42°C

Specific gravity: 1.70

Dry to touch: 2 hours

Over-coating time: 6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush Conventional spray Airless spray Roller

Thinner: Flagship Antifouling Thinners

Cleaning of tools: Flagship Antifouling Thinners

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.