



Dampseal

PRODUCT DATA

Description:

FLAG Dampseal is quick drying high performance interior coating which permanently covers damp, water and other household stains. Can be applied directly to damp walls and ceilings. Can be over coated with most oil and water based paint.

Application of 2 liberal coats would be required and brushed out approx. 30cms beyond affected area. Allow any new plaster to dry for 7 days prior to application.

Important: Please note, this product will not prevent rising damp or condensation.

Area of use:

Interior

Substrates:

Walls and Ceilings including plaster, cement and stone.

Packing:

2.5L

Physical Constants:

Colour:	White
Finish:	Satin
Volume solids:	50%
Theoretical spreading rate:	10 sq.metres per litre
Flash point:	N/A
Specific gravity:	1.2-1.24
Dry to touch:	1-2 hours
Overcoating time:	4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush
Thinner:	N/A
Cleaning of tools:	Water

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and fungal growth or solid matter like to interfere with the penetration of the sealer.

For additional guidance please contact your local Technical Sales Representative. Please check colour before use. If using multiple cans please check batch numbers are the same

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.