



## **Stain Blocker**

### **PRODUCT DATA**

---

#### **Description:**

To conceal unsightly stains that conventional emulsions will not cover, for example: - nicotine, smoke, marker pen, wax crayon, graffiti, tannin and bitumen. Apply Stain Blocker before painting to prevent stains from seeping through.

**Important:** Please note this product will not prevent stains caused by water damage unless the fault has been eradicated and the substrate allowed to dry.

#### **Area of use:**

Interior and exterior

#### **Substrates:**

Plaster and wood

#### **Packing:**

750ml

#### **Physical Constants:**

Colour:	White
Finish:	Satin
Volume solids:	45%
Theoretical spreading rate:	10 sq.metres per litre
Flash point:	N/A
Specific gravity:	1.2-1.24
Dry to touch:	1 hour
Overcoating time:	4 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### **Application Details:**

Application method:	Brush / Roller / Conventional Spray
Thinner:	N/A
Cleaning of tools:	Water

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*For additional guidance please contact your local Technical Sales Representative. Please check colour before use. If using multiple cans please check batch numbers are the same*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.