



Omni-White

PRODUCT DATA

Description:

Omni-White contains a biocode that protects the dried coating against fungal degradation. This paint is designed to resist cracking, peeling and blistering to avoid constant maintenance. Omni-White bonds to existing painted surfaces and promotes adhesion on a wide range of surfaces with minimal preparation. Omni-White also seals porous surfaces and is ideal for use in areas of persistent high humidity, frequent temperature changes and poor air circulation. Washable, scrubbable, stain and moisture resistant finish. Self-priming adheres to the surface with minimal preparation. A fade resistant coating. Water-based, low odour and quick drying

Area of use:

Interior / Areas of High Humidity

Substrates:

Plaster, wood, concrete, painted surfaces

Packing:

1 Litres & 2.5 Litres

Physical Constants:

Colour:	White
Finish:	Satin
Volume solids:	38%
Theoretical spreading rate:	Approx. 10 sq. metres per litre
Specific Gravity:	1.40
Flash point:	N/A
Dry to touch:	30 minutes
Over-coating time:	2 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush / Roller / Spray
Thinner:	Water
Cleaning of tools:	Water

Surface Condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

Please refer to the Material Safety Data Sheet for further information.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.