



Universal Primer

PRODUCT DATA

Description:

Universal Primer is a water-based primer-sealer for interior and exterior areas. It offers low odour application, quick drying convenience and promotes adhesion on difficult surfaces. Universal Primer effectively primes, seals and blocks stains for a wide variety of interior and exterior surfaces. A 'bond coat' primer that's great for hard-to-stick surfaces, offering excellent adhesion with minimal preparation. Also prevents rust formation when applied over clean ferrous metal such as iron and steel. Universal Primer contains a biocide that protects the dried coating against fungal degradation, making it ideal for high-humidity areas such as bathrooms and utility rooms. It offers effective resistance to fungal degradation on the underside and surface of the primer film, prolonging the life of your paint finish.

Area of use:

Interior / Areas of High Humidity

Substrates:

Plaster, wood, concrete, painted surfaces

Packing:

1 Litres & 2.5 Litres

Physical Constants:

Colour:	White
Finish:	Satin
Volume solids:	38%
Theoretical spreading rate:	Approx. 10 sq. metres per litre
Specific Gravity:	1.40
Flash point:	N/A
Dry to touch:	30 minutes
Over-coating time:	1 hour

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush / Roller / Spray
*Minimum DFT 75µm, adjust accordingly for rough surfaces

Thinner: Water

Cleaning of tools: Water

Surface Condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Do not apply in temperatures below 10 degree centigrade.

Please refer to the Material Safety Data Sheet for further information.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.