



2-STAGE DRINKING WATER
UNDER COUNTER FILTRATION SYSTEM

### 2-STAGE UNDER COUNTER DRINKING WATER SYSTEM W/FAUCET



## HALO UC-2 2-STAGE DRINKING WATER UNDER COUNTER FILTRATION SYSTEM



### FILTER HOUSINGS

1/4" QUICK CONNECT FITTINGS FOR EASY INSTALLATION

Durable 1/2 Turn Housings and Lids make change outs a snap. No Wrench Required.

Double O-ring seal provides for ideal filter to Housing Seal

Working Pressure up to 100 psi

MAX TEMP = 150° F

FILTER HOUSINGS MADE IN USA



HALO WATER SYSTEMS, LLC COPYRIGHT© 2013 ALL RIGHTSERSERVED



### **STOP WASTING MONEY ON BOTTLED WATER!**



LONG LASTING & RELIABLE DRINKING WATER FILTRATION SYSTEM INCLUDING FAUCET

HIGHLY EFFICIENT BACTERIOLOGICAL FILTRATION FILTRATION EFFICIENCY OF 100% AT 0.9 MICRON (SINGLE PASS METHOD)

HIGH QUALITY FILTER HOUSINGS
MADE IN USA

## STAGE 1 0.9 MICRON CYST RATED CERAMIC FILTER

THIS IS A HIGHLY EFFICIENT CERAMIC MICRO FILTER WHICH DELIVERS HIGHLY EFFECTIVE SUB MICRON FILTRATION OF DRINKING WATER. MANUFACTURED WITH THE HIGHLY CONSISTENT AND CONTROLLED PORE STRUCTURE THAT IS NECESSARY TO REMOVE A WIDE VARIETY OF WATERBORNE CONTAMINANTS OVER THE LIFE OF THE CARTRIDGE.

IN ADDITION TO FINE PARTICULATE MATTER, BACTERIA, CYSTS AND TURBIDITY ARE REMOVED TO A HIGH LEVEL OF EFFICIENCY. THE INCORPORATION OF SILVER LOCKED IN TO THE CERAMIC STRUCTURE INHIBITS THE GROWTH OF BACTERIA AND GIVES EACH CARTRIDGE ENHANCED BACTERIOSTATIC AND SELF STERILIZING PROPERTIES FOR SAFE HANDLING AND CLEANING. ABSOLUTE FILTRATION 0.9 MICRON. (0.5 MICRON ANSI STANDARD)

# STAGE 2 KDF55 & GRANULAR ACTIVATED CARBON FILTER

THE SECOND STAGE OF THE HALO UC2 IS A KDF 55 "/GRANULAR ACTIVATED CARBON CARTRIDGE THAT HAS SUPERIOR TASTE AND ODOR REMOVAL CAPABILITIES.

THE COPPER GRANULAR KDF IN THIS CARTRIDGE SPECIALIZES IN THE REMOVAL OF INORGANICS, HEAVE METALS AND CHLORINE. THIS LEAVES THE BLACK GRANULAR COCONUT SHELL ACTIVATED CARBON FREE TO DO WHAT IT DOES BEST, REMOVING ORGANIC MATTER. THESE FILTERS LAST AT LEAST 5X MORE THAN STANDARD CARBON BLOCK FILTERS. KDF MEDIA CONTROLS SCALE, BACTERIA AND ALGAE. EVEN IN HOT WATER.

KDF MEDIA CAUSES CELLULAR DAMAGE TO MICROBIOLOGICAL ORGANISMS WHICH CAN KILL OR INHIBIT ANY GROWTH. FOR MORE INFORMATION ON KDF MEDIA, GO TO WWW.KDFFT.COM

#### **CARTRIDGES - STAGE 1**

NSF Certified Standard 42 & 53 for the reduction of:

Particulates (Class I) 99.99% Cyst (Cryptosporidium & Giardia) 99.69% Turbidity 99.99% Harmful Bacteria (E. Coli, Cholera, Shigella, Salmonella, Klebsiella)

UC2 STAGE 1 CARTRIDGE SPECIFICATIONS:

1.3 GPM FLOW RATE
2" x 9,75" DIMENSIONS
OPERATING PRESSURE 10 PSI TI 125 PSI
CLEANABLE
>98% EFFICIENCY AT 0.2 MICRON
>90% EFFICIENCY AT 0.05 MICRON
100% ABSOLUTE FILTRATION EFFICIENCY AT 0.9
MICRON

#### CARTRIDGES - STAGE 2

### REMOVES/REDUCES:

SEDIMENT, CHLORINE, LEAD, MERCURY, ARSENIC, COPPER, SCALE, LIME, VOCS, THMS AND MUCH MORE!

UC2 STAGE 2 CARTRIDGE SPECIFICATIONS:

MICRON RATING: 10 NOMINAL DIMENSIONS: 9.75" X 2.75" WEIGHT: 2 LBS W/ 1 LB OF KDF MEDIA OPERATION TEMPERATURE: 40"F TO 100"F MAX. RECOMMENDED FLOW RATE: 1 GPM FILTER MEDIA: KDF-55 TM & GRANULAR ACTIVATED CARBON

Filter Life: 15,000 Gallons W/ 1 lbs of KDF media