

STEALTH unit



Features

- Inverse-Flow® Technology with 3½" filter depth
- Quick disconnect clamp ring design
- 1.0 micron final filtration
- Spin-on/spin-off element
- Equipped with brass petcock manual drain
- Removes oil contaminants as well as dirt & water
- Non-corrosive internal metal
- Heavy duty metal bowl construction

Applications

- Air tools, sand blasting, sanding impacts, buffing
- Ideal for mechanical section of shop

Benefits

- Cleaner compressed air with no water to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.5 % effective at water removal
- ½" BV-051 ball valve

Specifications

- Replacement Element: 6950-1
- Maximum Air Pressure: 200 PSIG
- Maximum Operating Temp: 125° F
- Maximum Flow: to 60 SCFM



Removes: ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 6900B	No Regulator
	STEALTH 6950B	Regulator w/ Gauge
	STEALTH 6952B	Regulator w/ Gauge, (2) 1/4" Outlets
3/8"	STEALTH 3050B	Regulator w/ Gauge
	STEALTH 3052B	Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6950-1

Removes: ● ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 6910B	No Regulator
	STEALTH 6960B	Regulator w/ Gauge
	STEALTH 6962B	Regulator w/ Gauge, (2) 1/4" Outlets
3/8"	STEALTH 3060B	Regulator w/ Gauge
	STEALTH 3062B	Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6960-1

Removes: ●

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 7000B	Regulator w/ Gauge
	STEALTH 7800B	No Regulator
1/2"	STEALTH 1000B	Regulator w/ Gauge
	STEALTH 1500B	Regulator w/ Gauge and manifold
3/8"	STEALTH 7030B	Regulator w/ Gauge

Replacement Element: 3C-060

Removes: ● ● ●

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain

3/8"	STEALTH 6060B	Regulator w/ Gauge
-------------	----------------------	--------------------

1st Stage Replacement Element: 6960-1
2nd Stage Replacement Element: 3C-060

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key: ● Water ● Dirt ● Oil



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

