

Care & Maintenance for Next Floor Luxury Flooring

Commercial Care and Maintenance

- Sweep or vacuum (without beater brush) at least once weekly or more often to remove loose dirt, sand and grit from the floor.
- Next Floor floors require regular and sufficient cleaning and maintenance to maintain safety and preserve the appearance of the floor. Damp wash floors with a quality non-oil based, detergent-free cleaner frequently in accordance to foot traffic and soiling. Rinse floors thoroughly with clean water after washing to remove all cleaners. Wipe spills promptly with a damp cloth to prevent staining.
- The recommended cleaner for all Next Floor products is Bona Stone, Tile & Laminate Cleaner. This cleaner will clean the floor without leaving any residue on the surface that can attract dirt and stains.
- The local conditions of your area will determine specific maintenance needs. Prepare an appropriate maintenance program that meets the needs of the specific facility.

Preventive care

- Ensure that all furniture legs have large surface, non-staining floor protectors in place. Floor protectors should have smooth, flat glides that are in complete contact with the floor. To avoid surface scratching of the floor, all glides should be equipped with self-adhesive felt protectors. Check felt protectors on movable furniture periodically for grit and wear and replace when necessary.
- Heavy appliances and furniture that are not moved often should have square 1 1/2" to 2 5/8" or round from 1 3/8" to 1 5/8" flat, non-staining composition furniture casters installed.
- Mobile appliances and furniture should be equipped with minimum 2" in diameter swiveling casters. Do not use ball-shaped casters.
- Place mats at outside entrances to prevent dirt, grit, water, snow, or ice from being tracked onto your floor.

Caution: Next Floor luxury flooring can be quite slippery when wet. Allow for adequate dry time after washing and wipe up all wet areas immediately. Improper cleaners or polishes may also cause slipperiness.

Residential and Light Commercial

Care For Immediately After Installation

- When returning heavy furniture and appliances to the room always use strips of plywood or hardboard to protect the floor. Install wide-bearing, non-staining felt protectors on all movable furniture.
- For our direct glue products void unnecessary foot traffic during the first 24 hours and wait 2-3 days before damp washing the floor to insure the proper adhesion of the glue. If necessary, spot clean during the first few days avoiding all seams.
- Foot traffic and cleaning is acceptable immediately after installation for Click / Floating Floors.

Preventive Care / Routine Maintenance

- Sweep or vacuum (without beater brush) at least once weekly or more often to remove loose dirt, sand and grit from your floor.
- The recommended cleaner for all Next Floor products is Bona Stone, Tile & Laminate Cleaner. This cleaner will clean the floor without leaving any residue on the surface that can attract dirt and stains.

Warning: Next Floor floors can be quite slippery when wet. Please use caution when walking on a wet luxury vinyl floor. Avoid oil-based cleaners, soap or detergent products as these may leave a dulling residue on your floor's finish. Do not use cleaners that contain abrasives or solvents which may permanently scratch or cause damage your floor.

- Check felt protectors on movable furniture periodically for grit and wear and replace when necessary.
- Heavy appliances and furniture that are not moved often should have square 1 1/2" to 2 5/8" or round from 1 3/8" to 1 5/8" flat, non-staining composition furniture casters installed.
- Mobile appliances and furniture should be equipped with minimum 2" in diameter swiveling casters. Do not use ball-shaped casters.
- Place mats at outside entrances to prevent dirt, grit, water, snow, or ice from being tracked onto your floor.

Caution: Next Floor floors can be quite slippery when wet. Allow for adequate dry time after washing and wipe up all wet areas immediately. Improper cleaners or polishes may also cause slipperiness.