



ARCHITECTURAL SPECIFICATIONS

RAINFOREST COLLECTION FLOATING RECYCLED LEATHER PLANKS AND TILES

SPECIFICATIONS

Style:	Floating Recycled Leather tiles a/o planks with cork backing
Description:	Recycled leather mounted on a formaldehyde-free high-density fiberboard backed with cork with Unielie® interlocking joint system
Thickness :	3/8"
Weight:	16 oz. per square foot
Nominal Sizes:	15" x 15" x 3/8" and 7.5" x 36" x 3/8"
Finish:	Water-based warranted floor protective finish (5 years commercial/ 25 residential)

**Custom sizes and colors available

PERFORMANCE CHARACTERISTICS

Taber Test (ASTM d 4060 – CS 17 wheel, 500 gr):	8,000 wear through cycles	
Static Load Limit (ASTM F970) :	005 inch	
Slip Resistance (ASTM C1028) :	Dry: 0.98	Wet : 0.98
Colorfastness (AATC- 100 hrs) :	Class IV	
Critical Radiant Flux (C –ASTM e 648) :	0.41 (Class II)	
Surface Burning Characteristics (ASTM E-84) :	Class C	
FIIC Test (ASTM E989): Test conducted over 8" concrete with <u>no</u> suspended ceiling	59 (no underlay)	61 (with underlay)
Low-VOC (California standard Public School 01350) :	Pass	

GREEN FEATURES

Our recycled leather Floating Tiles may contribute to LEED for Commercial Interiors in :

MR:	4.1/ 4.2	Recycled Content (pre-consumer)
IAC:	4.2 / 4.3	low-emission adhesive and product
Renewable:	6.0	Rapidly renewable resource and material

EcoDomo LLC is a member of the US Green Building Council and CoopAmerica. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.EcoDomo.com for more details.