

USER MANUAL

# WHIRLY VERB





## CONGRATULATIONS

on your purchase of Whirly Verb, a sweet-sounding reverb unit that also lets you get experimental with your sound.

Whirly Verb gives you an incredibly warm, rich small hall reverb that's specially tuned for the electric guitar. You can shape your reverb by controlling the decay time – and you can warp it to create all kinds of thick, layered sounds.

Take a quick look at the overview of controls in this user manual to familiarize yourself with Whirly Verb and its surprising capabilities.

## WHIRLY VERB CONTROLS

Your Whirly Verb features 4 separate controls, plus a MODULATION button to activate the modulation effect.

The REVERB knob lets you adjust how heavy a reverb effect you get, while the DECAY knob determines the length of your reverb trail. Turn these controls up to simulate a large concert hall or other large space, and down to get a smaller club or room effect.

The LEVEL knob is used to set the overall output volume from your Whirly Verb pedal. At 12 o'clock your output is the same as your input volume.

The MODULATION button and control knob let you turn your Whirly Verb into an effect that's much more dynamic and unusual than an ordinary reverb pedal. It can do everything from adding a slight lilt to your sound to creating weird, psycho effects that will take your guitar into another dimension.

The more you experiment with your Whirly Verb, the more you'll zero in on the reverb sounds that are perfect for your personal style.

## TECHNICAL SPECIFICATIONS

Input Impedance @ 1KHz	Higher than 1M Ohm
Output Impedance @ 1KHz	Lower than 1K Ohm
Power supply	9V DC (T-Rex FuelTank)
Minimum Power supply Voltage	8,5V DC
Maximum Power supply Voltage	12,5V DC
Current Draw @ 9V DC	90 mA
Maximum Input signal Vp/p	2Vp/p
Battery Type	9 V battery 6F22
Battery Life	30 to 60 min.
External connectors	Input Jack, Output Jack, 9V DC Jack
Controls	On/Off, Volume, Reverb, Modulation, Decay
Pedal size incl. knobs (W x H x D)	100 x 55 x 120 mm 3,9 x 2,2 x 4,7 inch
Weight excl. battery and packaging	0,335 kg / 11,8 oz

## T-REX WARRANTY CONDITIONS

T-Rex offers a 2-year warranty on all our products. In the unlikely event of a malfunction, please contact our technical support at [info@t-rex-effects.com](mailto:info@t-rex-effects.com) before sending us the product for repair. When the product has been sent to us at sender's cost, we will repair or replace your product and send it back to you - free of charge and usually within 3 weeks (shipping not included). The product needs to be accompanied by a copy of your receipt, serial number, return address, phone number, e-mail address and a brief explanation of the problem. Please note that we cannot replace a product until we have received it here in Denmark.

The warranty is lost if the product has been damaged by alteration, misuse, accident, or neglect; or if the product has been repaired or serviced by persons not authorized by T-Rex. Read more about warranty conditions at [www.t-rex-effects.com](http://www.t-rex-effects.com).

## ABOUT T-REX

Based in Vejle, Denmark, T-Rex Engineering makes classic and signature effects pedals for the world's best musicians. Our approach blends hi-tech innovation with old-world craftsmanship – always in the service of killer tone.

## EU REGULATIONS • ENVIRONMENT PROTECTION

T-Rex accepts and follows the regulations and directives issued by the EU. We find these environment protecting regulations very good, and we are happy to follow them.



ISSUED IN VEJLE, 2011

*Steen Meldgaard*

Steen Meldgaard Laursen  
Managing Director

*Lars Dahl-Jørgensen*

Lars Dahl-Jørgensen  
Development Director

*Sebastian Jensen*

Sebastian Jensen  
Production Director



T-Rex Engineering ApS  
[www.t-rex-effects.com](http://www.t-rex-effects.com)