

Issued in Vejle October 21th 2004

Steen Wulff

Managing Director

Lars Dahl-Jørgensen
Managing Director

Sebastian Jensen
Managing Director

T-Rex Engineering ApS, Tel.: +45 75 72 71 81, Fax: +45 75 72 71 98
www.t-rex-engineering.com, mail: info@t-rex-engineering.com

Users manual

Room-Mate





HIGH CUT filters out the high frequencies from your reverb trail for that great vintage sound.

STEREO OUT

Room-Mate features stereo outputs, making it ideal for both recording and live stereo setups.

Use stereo outputs whenever possible for an even bigger, more life-like sound. Input is mono only.

Note:

Room-Mate comes with a specially selected preamp tube, with a guaranteed life of at least ten years.



Warranty

Our manufacturer's warranty gives you a two-year guarantee against defective parts or workmanship. If you experience a problem, contact your nearest T-Rex dealer.



Congratulations on your purchase of Room-Mate, the gold standard in tube-driven reverb for guitarists.

Room-Mate marries cutting-edge digital technology and superior analogue craftsmanship to deliver a superb vintage reverb.

The four classic presets are warmed by a built-in tube, and additional parameters help you shape the perfect reverb for your sound.

Turn the page for an overview of the controls.

RoomMate controls

MODE is where it all starts. You can choose between the following presets:

- Classic Plate – excellent medium plate reverb
- Warm Hall – big and warm for a great live sound
- Bright Hall – expansive hall with incredible detail
- Chorus with Warm Hall – enhance your acoustic

MIX controls the blend of clean signal and reverb.
The more you turn it up, the bigger the sound.

LEVEL sets the level of the signal sent to your amp or studio mixing board.

Size

Box 100x120x35mm + Switches/knobs on top.
16mm + Knobs on bottom 3mm.

Controls

MIX, LEVEL, HIGH CUT and MODE.

Modes

Classic Plate, Warm Hall, Right Hall and Chorus with warm Hall.

Connections

INPUT-Jack 6,3 mm. OUTPUT-Jacks 6,3 mm left/right.

Power supply

The pedal comes with an external power supply giving 12 volt DC and 800 mA. The power supply runs on 100/115/230V AC/50-60Hz dependant on country.

Effect usage

12 volt DC, 300 mA, 5 Watts.

Weight

660 gram packed in box.