



**STANDARD BRAKE SAFE® KITS
BRAKE CHAMBER IDENTIFICATION &
BRAKE STROKE RE-ADJUSTMENT LIMITS**

TYPE SIZE	CHAMBER MARKING	OUTSIDE DIAMETER	OEM LIMIT (Manufacturer)	(DOT) ADJUSTMENT LIMIT	BRAKE SAFE KIT	
					TRUCK	TRAILER
16	None	6 3/8" (162 mm)	2 1/4"	1 3/4" (45 mm)	PU242	N/A
16L	'L' and Stroke Tag	6 3/8" (162 mm)	2 1/2"	2" (51 mm)	PU302	N/A
20	None	6 25/32" (172 mm)	2 1/4"	1 3/4" (45 mm)	PU242	N/A
20L	'L' and Stroke Tag	6 25/32" (172 mm)	2 1/2"	2" (51 mm)	PU302	N/A
24	None	7 7/32" (183 mm)	2 1/4"	1 3/4" (45 mm)	PU242	N/A
24L	'L' and Stroke Tag	7 7/32" (183 mm)	2 1/2"	2" (51 mm)	PU302	N/A
24LS	Square Ports, Tag & Marking	7 7/32" (183 mm)	3"	2 1/2" (64 mm)	PU250LS	N/A
30	None	8 3/32" (205 mm)	2 1/2"	2" (51 mm)	PU302	TL302* ¹
30	'DD3' (Bus /Coach)	8 1/8" (206 mm)	2 3/4"	2 1/4" (57 mm)	PU302	N/A
30LS	Square Ports, Tag & Marking	8 3/32" (205 mm)	3.0"	2 1/2" (64 mm)	PU250LS	TL250LS* ¹
* VANTRAAX OR INTRAAX TRAILER APPLICATIONS USE TL302-CP OR TL250LS-CP						
¹ "SUPER SINGLE WHEEL" TRAILER APPLICATIONS USE TL302S OR TL250LSS						