

Vintage's Wire Brushed floors are another unique and beautiful option for a textured floor. The brushing technique with its UV Urethane Oil finish is a perfect mix, as the UV Oil enhances the wood, preserving the natural look and feel of the brushing. These floors tend to hide dents and scratches extremely well and everyday wear is blended in. Wire brushing is very conducive to achieving 2 tone floors, giving you a European style and look.

White Oak, Atlantis

| RED OAK | | ASH | | WHITE OAK | | WHITE OAK RIFT & QTR SAWN | |
|------------|----------|-------------|-----------|-------------|------------|---------------------------|--|
| NATURAL* | TITAN | GLASGOW | ORION* | ZEUS* | NATURAL | | |
| KAHLUA* | GRYPHON* | KALAHARI | ATLANTIS* | GOTHAM* | NAUTILUS | | |
| CHARIOT* | PEWTER* | MANCHESTER | PHARAOH* | BUCKINGHAM* | GOTHAM | | |
| BERKSHIRE* | COCOA* | COBBLESTONE | | BAROQUE* | BUCKINGHAM | | |
| MOJAVE* | VENUS* | COVENTRY | | SPARTACUS | BAROQUE | | |
| | ZAMBEZI* | BOARDWALK | | | | | |

* Herringbone: These species and colors are available in Herringbone. Refer to the Herringbone specification sheet for more information.

WIRE BRUSHED SPECIFICATIONS

Product Type:

3/4" (19mm) Pioneered® Solid
 3/4" (19mm) Northern Solid Sawn®
 3/4" (19mm) Solid Sawn®
 3/4" (19mm) Northern Solid Sawn® Herringbone

*Refer to availability chart for details

Product Species & colors:

Ash: Boardwalk, Cobblestone, Coventry, Glasgow, Kalahari, Manchester
 Red Oak: Natural, Kahlua, Chariot, Berkshire, Cocoa, Gryphon, Pewter, Titan, Mojave, Venus, Zambezi
 White Oak: Atlantis, Baroque, Buckingham, Gotham, Orion, Pharaoh, Zeus, Spartacus
 Rift & Qtr. Sawn White Oak: Natural, Baroque, Buckingham, Gotham, Nautilus

Product Grade & Width:

Ash - Pioneered® Select-V 2 1/4" , 3 1/4" , 4 1/4"
 Red Oak - Pioneered® Select-V 3 1/4"*
 Pioneered® Heritage 3 1/4"*
 White Oak - Northern Solid Sawn® Select-V 3 1/4"
 Northern Solid Sawn® Character 5"
 Solid Sawn® Character 7"
 Solid Sawn® Rift & Qtr. Sawn Select-V 5" , 7"

Product Lengths:

Pioneered® Solid Select-V: 12"-79" average 32"
 Pioneered® Solid Heritage: 10"-84" average 30"
 Northern Solid Sawn® Structured: Select-V 15" - 70" average 37"
 Northern Solid Sawn® Structured: Character 20"-83" average 42"
 Solid Sawn® Structured: Rift&Qtr. Select-V 14"-78" average 38"
 Solid Sawn® Structured: Character 18" - 8" average 44"

Product Gloss:

UV Urethane Oil

Product Construction:

Tongue & Groove, microbevel on 4 sides

Installation Method:

Pioneered® Solid - Nail
 Northern Solid Sawn® & Solid Sawn® - Nail, Glue or Float
 Herringbone Northern Solid Sawn® - Glue

Structural Warranty:

Lifetime

Lifetime Stability Warranty:

Relative humidity must be maintained between
 40% - 50% for Pioneered® Solid
 25% - 70% for Northern Solid Sawn® and Solid Sawn®

Residential Warranty:

10-Year Wear Warranty

Commercial Warranty:



1-Year Wear Warranty

Care & Maintenance:




See Vintage UV Oil Care & Maintenance instructions



Relative Humidity Chart



Relative Humidity Chart



Consult Vintage's radiant heat compliance information available at www.vintageflooring.com

