

I-30HD Integrated Amplifier



Specifications:

- . Power Output: RMS 30W per channel from 20Hz-20kHz
- . Frequency Response: 20Hz-30kHz (+/-0.5dB 1W)
- . Output Power Distortion: 1% (10W 1KHz)
- . Input Sensitivity: 220mV
- . Input Impedance: 100k ohms
- . Inputs: Line1, Line2, Line3, AUX, USB DAC
- . MAX. Line Input: RMS 3.5V
- . USB DAC Spec.: 32Bit 384kHz
- . Speaker Output Impedance: 4ohms or 8ohms
- . Headphone Output Impedance: 32-600ohms
- . Overall Negative Feedback: -40 dB
- . Overall S/N Ratio: 86dB
- . Power Consumption: MAX.180W
- . Power Requirements: 110-120VAC 60Hz/220-240VAC 50Hz
- . Operation Method: Class A PUSH/PULL
- . Power Tubes Required: 2 Matched either 6L6G/5881/EL-34
- . Preamp & Driver Tubes Required: 12AX7x2 (ECC83 x2), 12AU7 x2
- . Tube Bias: Automatic
- . Dimensions: 380x295x160mm(WxDxH)
- . Weight: 17kg

WorldWide Sales & Marketing Office: Hong Kong

Luen Hing Electrical (HK) Limited
Address: G/F., 152 Apliu Street, Shamshuipo, Kowloon, Hong Kong
Tel: +852 2728 8745 Fax: +852 2729 2962
Email: worldsales@dared.com.hk

South East Asia Sales Office: Singapore

Address: 19 Burn Road, 01-01 Advance Building
Singapore 369974
Tel: +65 6844 1623 Fax: +65 6281 3371
Email: seasales@dared.com.hk