



PRODUCT DESCRIPTION

Fired Earth Gloss Enamel is a classic alkyd pigmented solvent based enamel. It is a hard wearing high gloss enamel which has excellent adhesion and water resistance for interior & exterior areas. It is meant for application to both primed new work and sound previously prepared painted areas.

PRODUCT BENEFITS

- Lead free
- Hard wearing gloss finish
- Water & steam resistant
- Excellent adhesion properties

USES

Interior and exterior surfaces:

Walls, doors, window frames, gates, handrails, fascias, tables, trims and shelves.

It may also be used on new or previously painted metal, wood, masonry, plaster, gypsum, concrete, fibre cement and brick surfaces after suitable preparation.

SURFACE PREPARATION

Surfaces must thoroughly dry (15% moisture max), clean and in sound condition before painting.

New Surfaces	Primer/System
<ul style="list-style-type: none"> • Concrete/Cement Plaster • Fibre Cement • Gypsum Plaster/Rhinolite 	Apply one coat of Fired Earth Plaster Primer , followed by two coats of Fired Earth Gloss Enamel .
New Wood-Exterior	Sand wood smooth, apply one coat of a quality pink or white wood primer followed by a coat of Fired Earth Universal Undercoat and two coats of Fired Earth Gloss Enamel leaving overnight between all the coats.
New Wood-Interior	Sand wood smooth followed by a coat of Fired Earth Universal Undercoat and two coats of Fired Earth Gloss Enamel leaving overnight between all the coats.
Galvanised & Mild Steel	Apply one coat of a quality Anti-Corrosive Multi-Purpose Primer , followed by one coat of Fired Earth Universal Undercoat and two coats of Fired Earth Gloss Enamel leaving overnight between all the coats.

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing all dirt, grease, mould, grime and flaking paint before starting to paint. Spot prime bare plaster, wood or metal with the appropriate quality primer then one coat of **Fired Earth Universal Undercoat** and two coats **Fired Earth Gloss Enamel** leaving overnight between all the coats.

MIXING

Stir the contents thoroughly with a flat paddle before use.

APPLICATION

Apply with a quality brush, mohair or fine foam roller on smooth surfaces. For rough surfaces use a long pile synthetic wool roller. This product may be sprayed. Always allow overnight drying between coats.

SPREADING RATE

This product will cover approximately 8 m² per litre per coat depending on the type of substrate and surface porosity. Spreading rates are based on a roller application to smooth substrates.

DRYING PROPERTIES

Surface or touch dry: 4 - 6 hours.
Recoating time overnight.

CLEANING

Clean all tools (brushes & rollers) while wet with Mineral Turpentine after use.



DO NOT PAINT IF

1. The temperature is below 10°C or above 35°C.
2. The surface is damp.
3. It is raining or rain is forecasted.

HEALTH & SAFETY

*Allow good ventilation when painting in-doors.




WEAR PROTECTIVE CLOTHING

GUARANTEE 7 YEARS

Call the Fired Earth Guarantee & Advisory Service Line on 0860 77 72 23 to register your guarantee. The guarantee must be registered within 30 days of the purchase of this product. Terms and conditions apply, available on request from your stockist or visit www.fired-earth.co.za.



Our environmental programme, designed to inform and assist you to shop more responsibly and show you how you can make a valuable contribution towards sustaining our planet's resources

LID	BUCKET	PRODUCT	
TIN	TIN	PAINT	
WIDELY RECYCLED	WIDELY RECYCLED	NOT RECYCLED	

www.eco-wise.co.za



DISPOSE OF CONTENTS RESPONSIBLY



INTERIOR & EXTERIOR USE



PAINT & SPRAY



TOUCH DRY 4-6 HOURS



WATER & STEAM RESISTANT