

ROOF X TENDER[®] 915

Fluid Flash[™] Detail Sealant

DESCRIPTION:

ROOF XTENDER[®] 915 Fluid Flash[™] Permanent Detail Sealant is a maximum performance, high build, liquid applied waterproofing sealant. This highly flexible and seamless waterproof sealant is designed to coat, seal and protect complex details that would normally require intricate flashing systems. It is a FAST, EASY and PERMANENT way to seal base flashings, curbs, penetrations, seams, HVAC Units, tie in dissimilar surfaces, and to make all kind of repairs. Engineered with "Green" solvent-free, moisture cure polymers, Fluid Flash[™] is ideal for the contractor that demands maximum performance, ease of use and innovative technologies that benefit our workplace and our environment. Fluid Flash[™] can be used in new construction as well as restoration and maintenance applications. Fluid Flash[™] provides excellent adhesion to most common building materials and can be used on roof, window, door and wall applications.

Fluid Flash[™], FAST, EASY and PERMANENT!

USES:

Ideal for sealing & waterproofing these and many other difficult to access areas:

- Flashings
- Sky Lights
- Pitch Pockets
- Gutters
- Air Conditioners
- Brick Ties
- Roof Vents
- Penetrations
- Ductwork
- Roof Hatches
- Chimneys
- Seams

APPLICATION:

Fluid Flash[™] can be dispensed manually. Simply cut a small hole at the top of the sausage with a utility knife and squeeze. It may also be applied by using ROOF XTENDER'S[®] sausage type caulking gun or other sausage gun. The substrate must be clean and free from grease and oils. Metals must be de greased with a suitable solvent. May be applied with a brush or trowel. Roofing granules may be embedded in top layer. Clean with xylene. For Professional Use Only.

SPREAD RATE & COVERAGE:

Contains 12 Sausages per container. Approximately 1 Sausage per penetration.

Dry Mills Coverage (1 Sausage Pack):

1 Pack @ 62.5 mills = Approx. 2.0 sq. ft.

1 Pack @ 125 mills = Approx. 1.0 sq. ft.

1 Pack @ 250 mills = Approx. 0.5 sq. ft.

Dry Mills - Per Case (12 Sausage Packs ≈ 1 gal.):

12 Packs @ 62.5 mills = Approx. 25 sq. ft.

12 Packs @ 125 mills = Approx. 12.5 sq. ft.

12 Packs @ 250 mills = Approx. 6.25 sq. ft.

PERMANENT REPAIR SYSTEM:

Step 1: Cut a piece of RXT polyester fabric to extend over and a minimum of 2" past all damaged areas. See specific RXT Detail Sheet for polyester requirements on or around penetrations, cant strips, tie in's or other detail areas.

Step 2: Dispense Fluid Flash[™] onto surface, brushing it over and 3-4" past the damage or area to be sealed. Use one sausage for every one square foot. Masking tape can be used to keep detail work looking professional.

Step 3: Immediately embed polyester fabric over damaged area and into wet sealant. Brush polyester to eliminate all wrinkles, voids, blisters, etc.

NOTE: RXT Fleece Back Tape may be used in lieu of step 1 & 2.

Step 4: Seal the top of the polyester with an additional application of Fluid Flash[™] Detail Sealant at one sausage per each one half square foot over the top of the reinforcement and a minimum of one half inch past the edge of the polyester. Surface should be completely smooth and the fabric pattern should not be visible. Embed roofing granules immediately into the Fluid Flash while wet.

Step 5: If applying a field coating, leave the top polyester surface of tape or reinforcement exposed. Do not top coat with Fluid Flash.



- FAST & EASY TO USE
- NO WASTE SAUSAGES
- SOLVENT FREE POLYMERS
- SINGLE COMPONENT



FIRST AID TREATMENT: If in eyes, immediately flush with running water for 15 minutes. If on skin, immediately wash affected area with soap and water. If ingested, immediately give two glasses of water for dilution and do not induce vomiting. Seek medical treatment immediately.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

WARNING:

This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

WARNING:

MAY IRRITATE EYES AND SKIN. MAY BE HARMFUL IF SWALLOWED. USE WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. FOR EXTERIOR USE ONLY.

SPECIFICATION DATA: ASTM C 920

Weight Per Gallon

12.3 - 12.8 lbs/gal

Color

Grey

Elongation

500%

Consistency

Brush, Gun or Trowel

Skin Time (50% Relative Humidity, 70°F)

30 min.

Full Cure (50% Relative Humidity, 70°F)

3 - 7 days

Application Temperatures

40°F - 110°F

Flashpoint

.450°

Application Temperatures

40°F - 110°F

Flashpoint

>450°

SHIPPING WEIGHTS:

1 gallon pail (3.78L)

12.8 lbs.

VOC/VOS

Less than 17.0 grams per liter

POLYMER

C.A.S.# MIXTURE