

PRO-TECT™

FIBRE WALLCOVERING
EU & UK STANDARDS

- Perfect for cinemas
- Masks scratches, scrapes and bumps
- Protects high traffic areas
- Impact resistant and self-healing
- Low maintenance
- Does not fray or ravel
- Pill and fuzz resistant
- Colourfast and stain resistant
- Velcro compatible and tackable
- Soft and hardwearing
- Disguises soiling
- 100% recyclable
- Ideal for flat or curved surfaces
- Available in 3 standard colours



PRO-TECT
Wall Protection



TECHNICAL SPECIFICATIONS

Style: Ribbed Loop Construction

Thickness: 5.00 mm

Backing: Latex

Weight: 1008 g/m²

Roll width:

1 m x 30 Lin. m

2 m x 30 Lin. m

PERFORMANCE TESTS

EU Flammability EN 13501

Euroclass Rating: B

Smoke: s1

Droplets: d0

CE Certified

FEATURES

PRO-TECT is a hardwearing wall finish specifically engineered for high traffic areas. Soft, flexible and attractive.

Perfect for cinemas. Protect wall surfaces with this durable self-healing finish.

COLOURS

PRO-TECT is available in 3 standard colours - black, charcoal and midnight blue.

Custom colours are available upon request and review. Minimum order quantities may apply.

INSTALLATION

1. Direct glue to plasterboard, concrete or masonry.
2. Wall must be sound, clean and free from dust and dirt.

Recommended adhesives:

Laybond 81 (Plasterboard)

Laybond 48 (Concrete or masonry)

DESIGN

eomac's in-house Technical Team can provide design and layout support. Contact **eomac** for inquiries.


MAINTENANCE

Vacuum-clean.

Can be cleaned with carpet detergent. Do not use solvents containing acetone or hydrogen peroxide.



MADE IN THE UK



PRO-TECT
Wall Protection

PRO-TECT
Wall Protection

For more information on PRO-TECT, please contact us.
www.eomac.com | eomac@eomac.com