

COLORLOCK

COLORLOCK is a 2-component water based paver sealer designed for use on concrete pavers, porous stone, brick and cement textures. **COLORLOCK** dries crystal clear and is non-yellowing and non-whitening. It can be applied same day over surface dry substrates and will promote joint stabilization.

SURFACE PREPARATION: Pavers must be clean, dry and free of built up sealers. Pressure cleaning is the most effective method of cleaning. A chemical method may be necessary if stains and marks remain on the surface after cleaning. Efflorescence must be removed prior to the sealing process.

MATERIAL MIXING: **COLORLOCK** is a two-component kit that must be mixed together before application. Mix part A with part B using a paddle mixer or stirring stick (vigorously) for 2 minutes. Part A is 4 parts and part B is 1 part, no measuring is necessary if you are activating a complete kit. Once the sealer is mixed, dilute the mixture once again with one part mixed sealer with one part water. Only mix what can be used within a 2 hour period. Warning: If you use sealer undiluted, a slippery condition will occur.

APPLICATION: **COLORLOCK** may be applied by brush roller or sprayer. It goes on milky white and dries completely clear. Apply evenly as to minimize puddles, roller trails and drips. Apply with minimum overlapping strokes to maintain an even film formation. Excess application and puddling can be “laid off” by using a dry roller or brush.

COVERAGE: On most unsealed pavers coverage will be 250 - 300 square feet per gallon of diluted sealer. Second coat coverage or previously sealed surfaces can be as high as 400 square feet per gallon.

DRY TIME: Dry to the touch 2 to 4 hours. Product will be unaffected by rain once it is dry to the touch. Recoat time is 2 to 4 hours. Cure time for foot traffic 24 hours. Cure time for vehicular traffic is 48 to 72 hours.

CLEAN UP: Clean tools and sprayer with regular tap water. Thoroughly clean sprayers until tap water runs clear. Solvent 100 or Xylene for final run through. Left over sealer cannot be saved and should be discarded once hard and in solid form.

Limitations: Do not use on visibly wet surfaces or surfaces with trapped moisture within 4 inches of the surface. Always apply a test to the substrate to insure that desired appearance is achieved. Some pavers accept sealers differently than others and a particular change in appearance is not guaranteed.

TECHNICAL:

Weight Per Gallon: 8.75
Solids By Weight: 40% +/- 2%
VOC: < 50 g/l

PACKAGING:

1-Gal Kit
5-Gal Kit
1 QT Sample Kit

WARNING: Whenever a surface is coated it may become slippery. Non skid additives should be used to prevent this from happening. It is the sole responsibility of the applicator to determine whether non-skid additives should be used.

CAUTION: Keep out of reach of children. Do not take internally. If swallowed, contact a physician immediately. Close container after each use. Wear eye protection, if eye irritation occurs, flush with water and call a physician if irritation persists. Avoid prolonged contact with skin and use a NIOSH approved respirator.

LIMITATION OF LIABILITY: Technical data is true and accurate to the date of issuance but subject to change without notice. Our products conform to our quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor or consequential damages is excluded.