

# GC800 Series



### FEATURES & OPTIONS

- UL Listed (UL 10C)
- Universal application & non-handed installation
- Constructed with precise aluminum die-cast body with steel arm
- A heat-treated steel rack & pinion immersed in high-grade oil operate a nest of coils to give a smooth precise action & minimum wear
- Stable hydraulic fluid for any climatic operation & constant lubrication
- Adjustable closing and latching speed
- Stable hydraulic fluid capable of withstanding temperature ranges of 105 degrees F. to -25 degrees F.
- Application: Most economical door closer designed for light duty interior application

### PACKAGE INCLUDES

- Parallel bracket
- Wood screws and machine screws

### FINISHES

- Aluminum (painted)
- Dark Brown (painted)
- Gold Brass (painted)

Description	GC802	GC803	GC804
Door weight range (lbs)	44~100	88~143	132~187
A. Length of door closer body	7-3/8"	8-13/16"	9-7/8"
B. Height of door closer body	1-3/4"	1-3/4"	1-7/8"
C. Horizontal mounting holes	6-5/8"	8-1/8"	9-1/16"
D. Vertical mounting holes	3/4"	3/4"	3/4"

### WARRANTY

- 10 years mechanical warranty
- Five years finish warranty



### CODE COMPLIANCE

- ANSI A156.4 Grade 2
- UL10C and UBC 7.2 for positive pressure

### SPECIFICATIONS

**Closer:** Closers shall be by Pamex model # GC802, GC803 or GC804, full rack and pinion type with cast aluminum alloy body. All closers shall be provided with non-critical valves adjustment to independently regulate the sweep, latch and back-check.

### APPLICATION

Most economical door closer designed for light-duty interior application

