Dallas *FLN Series*



FEATURES & OPTIONS

Latch Backset

Exterior: Adjustable UL deadlatch standard Interior: Adjustable UL plainlatch standard (other options available)

Faceplate

1" x 2-1/4" round corner standard (other options available)

Bolt

1/2" throw

Door Thickness

Fit 1-3/8" to 1-13/16" standard

Cylinder

6-pin SC "C" keyway solid brass cylinder standard 5-pin KW keyway available

Strike Plate

1-3/4" x 2-1/4" full lip round corner standard (other options available)

Handing

Reversible for right or left handed doors

SPECIFICATIONS

Lockset: Lock or latchset shall be by **PAMEX** model # **FLN Series**. All locks shall provide with 3 hour rated solid brass plain or deadlatch. Lock chassis shall have individual springs for lever return to prevent lever sag.

FINISHES

(other finishes available upon request with lead-time)

- □ US10B 613 Oil Rubbed Bronze \$
- □ US15 619 Satin Nickel \$\frac{1}{2}\$

CODE COMPLIANCE

- Meets ANSI/BHMA A156.2,
 Series 4000, Grade 2
- Meets ADA Requirements
- UL 3-Hour Fire Rated

<u>WARRANTY</u>

- Lifetime mechanical warranty
- Five years finish warrant





FUNCTIONS

Entry - FLN0B/FLN0C (F190) \$

Outside lever locked or unlocked by key outside or turn-piece (FLN0B) / push-button (FLN0C) inside. Inside always free.

Privacy - FLN1B/FLN1C (F76)

Outside lever locked or unlocked by **turn-piece (FLN1B)** / **push-button (FLN1C)** inside or by a coin or screwdriver outside. Inside always free.

Passage - FLN3B (F75)

Both levers always free.

Communicating Passage – FLN3BH

Blank plate outside. Inside lever always free.

Half Dummy - FLN4B

Single dummy trim for pull only.

Double Dummy - FLN4BD

Double dummy trim for both sides of the door.

Storeroom - FLN5B (F86) 2

Outside lever always fixed and unlocked by key only. Inside lever always free.

Classroom – FLN8B (F84) \$

Outside lever locked or unlocked by key. Inside lever always free.

