

Belle

FT6 Series



FEATURES & OPTIONS

Door Preparation

Cross Bore: 2-1/8", Edge: 1"

Latch Backset

Exterior: 2-3/8" deadlatch standard
Interior: 2-3/8" plainlatch standard
(other options available)

Faceplate

1" x 2-1/4" round corner standard
(other options available)

Bolt

1/2" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard
(extension kit available for 1-3/4" to 2-1/4" door)

Cylinder

5-pin KW keyway solid brass cylinder standard
5-pin SC "C" keyway available

Strike Plate

2-1/4" x 1-3/4" round corner full lip standard
(other options available)

Handing

Non-Handed

MANSI/BHMA

A 156.2 Grade 3

FINISHES

(other finishes available upon request with lead-time)

- US3 – 605 – Polished Brass
- US5 – 609 – Antique Brass
- US32D – 630 – Satin Stainless Steel

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

FUNCTIONS

Entry

Both knobs locked or unlocked by key outside or turn-piece inside.

Privacy

Both knobs locked or unlocked by turn-piece inside. Outside lever unlocked by coin or screwdriver.

Bathroom-Split Finish

Same function as Privacy. Inside knob is Polished Chrome.

Passage

Both knobs always free.

Half Dummy

For doors where only pull is required.

