

GC6800 Series



FEATURES & OPTIONS

- UL Listed (UL 10C)
- Universal application and non-handed installation (regular and parallel bracket included)
- Multi-size strength, power adjustable for size 1 thru 6 (factory preset size 3)
- Double heat-treated steel, tempered springs
- Heat-treated steel piston and pinion
- Adjustable back check standard
- Tri-packed standard (for regular arm, top jamb, or Parallel mounting)
- Adjustable closing and latching speed
- Optional delay action
- Door weight range from 44 ~ 265 lbs.
- Application: Reliable heavy duty door closer designed for retail storefronts, schools, hospitals, and other high-use applications

PACKAGE INCLUDES

- Parallel bracket
- Wood screws and machine screws
- Full plastic cover
- Sex bolts and Thru bolts

FINISHES

- AL - Aluminum (689)
- DB - Dark Brown (695)

WARRANTY

- 25 years mechanical warranty
- Five years finish warranty



ADA

CODE COMPLIANCE

- ANSI A156.4 Grade 1
- UL10C and UBC 7.2 for positive pressure
- Meets ADA barrier-free accessibility



SPECIFICATIONS

Closer: Closers shall be by Pamex model # GC6800, full rack and pinion type with cast aluminum alloy body. All closers shall be provided with non-critical valves adjustment to independently regulate the sweep, latch and back-check. Closer shall have full spring adjustment from size 1 to 6 for barrier free (BF).

